

S 自行剪叉式升降平台 Self-propelled Scissors Lift



技术参数/Technical Parameter

产品型号 Model	SPSL06A	SPSL06	SPSL08A	SPSL08	SPSL10	SPSL12
最大工作高度 Working Height Maximum	8.00m	8.00m	10.00m	10.00m	12.00m	14.00m
最大平台高度 Platform Height Maximum	6.00m	6.00m	8.00m	8.00m	10.00m	12.00m
安全工作载荷 Safe working load	230kg	230kg	230kg	230kg	230kg	230kg
延伸平台安全工作载荷 Extended platform safe working load	100kg	100kg	100kg	100kg	100kg	100kg
工作平台尺寸(长×宽×高) Working platform size(L*W*H)	2.26×0.81×1.1m	2.26×1.13×1.1m	2.26×0.81×1.1m	2.26×1.13×1.1m	2.26×1.13×1.1m	2.26×1.13×1.1m
整机外形尺寸(长×宽×高, 护栏未折叠) Overall size	2.475×0.81×2.158m	2.475×1.15×2.158m	2.475×0.81×2.286m	2.475×1.15×2.286m	2.475×1.15×2.414m	2.475×1.15×2.542m
整机外形尺寸(长×宽×高, 护栏未折叠) Overall size	2.475×0.81×1.708m	2.475×1.15×1.708m	2.475×0.81×1.836m	2.475×1.15×1.836m	2.475×1.15×1.964m	2.475×1.15×2.094m
台面延伸尺寸 Length extension deck	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m
最小离地间隙 Ground clearance-center	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m	0.1/0.02m
轴距 Wheelbase	1.89m	1.89m	1.89m	1.89m	1.89m	1.89m
转弯半径(内轮/外轮) Turning radius (inner / outer wheel)	0/2.1m	0/2.2m	0/2.1m	0/2.2m	0/2.2m	0/2.2m
起升/驱动电机 Lifting / driving motor	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw	24V/4.5kw
升降速度 Lifting speed	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min
机器行驶速度(收拢状态) The machine speed (folded state)	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
机器行驶速度(起升状态) Machine travel speed (lifting state)	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
蓄电池 Battery	4×6V/225ah	4×6V/225ah	4×6V/225ah	4×6V/225ah	4×6V/225ah	4×6V/245ah
充电器 Charger	24V/25A	24V/25A	24V/25A	24V/25A	24V/25A	24V/25A
最大爬坡能力 Max Climb Capability	25%	25%	25%	25%	25%	25%
工作最大允许角度 Maximum allowable working angle	1.5° /3°	2° /3°	1.5° /3°	2° /3°	2° /3°	1.5° /3°
轮胎 Tyre	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm
整机重量 Weight	1685kg	1900kg	1845kg	2060kg	2300kg	2460kg

产品特点/Product Features

自行剪叉式升降平台具有自动行走功能，整机一体式设计，内置电瓶电源，满足在不同工作状态下，不需外接电源，不需外来动力牵引即可升降自如，而设备的行走转向也只需一人便可完成。操作人员只需掌握好设备前的控制手柄即可完成设备前进、后退、转向、快、慢速行走和上下等动作。自行剪叉式升降平台移动灵活，操作方便、省工、省力令高空作业更方便快捷，是现代企业高效安全生产之理想高空作业设备。

Self-propelled scissors lift Has the function of automatic walking machine, integrated design, built-in battery power, meet in different working conditions, no external power supply, no external power traction can lift freely, and the equipment running and steering is also just a person can be completed. The operator only needs to master the control handle to the equipment before the complete equipment forward and backward, steering, fast, slow walk and equal action. Self scissors type lifting platform is mobile and flexible, convenient operation, labor saving, make high-altitude operations more efficient and convenient, is the ideal equipment for high-altitude operations, the safety production of the modern enterprise.

Easy Pull Out Chassis



Hydraulic System Brand Bucher



Battery Brand Trojan



Platform Controller



Emergency Down



Pothole protection device



M 迷你自行剪叉式升降平台

Mini self-propelled scissor lift platform



技术参数/Technical Parameter

产品型号	Product Model	SPSL03	SPSL04	SPSL06
台面尺寸mm	Mesa size mm	1290*700	1290*700	1670*740
载重kg	Load kg	240	240	230
净高度m	Net height M	3	4	5.8
外形尺寸mm	Contour dimension mm	1435*760*1900	1435*760*1980	1860*760*2180
台面延伸mm	Mesa extension mm	600	600	900
重量kg	Weight kg	805	860	1435



产品特点/Product Features

- 质量轻、体积小单人可以轻松灵活的移动至作业点;
- 业内最小的平台尺寸1.15m × 0.60m, 适合在狭小的空间作业;
- 抽屉式底盘方便维护;
- 故障代码自动显示方便检修。
- Light weight, small volume,it can be moved flexibly to the operation position by single person.
- The Minimum size of platform in the industry,1.15mX0.60m, so it is fit for operating in narrow space.
- Drawer type chassis is easy to maintain.
- Fault code display automatic,convenient to check and repair.

